

Section

MV Outer sheath

ApplicationField
Laboratory
Production**PRODUCT BENEFITS**

Quick, light and easy to use

TOOL CAPACITY

Diameter	26 - 52 mm 1,024 - 2,047 inch
Circular cutting thickness capacity	2,5 mm / 0,098 in
Longitudinal cutting thickness capacity	3,0 mm / 0,118 in

TOOL DIMENSIONS

Length	265 mm
Width	95 mm
Height	80 mm
Weight without box	0,6 Kg
Packaging	Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE
Phone: +33 2 43 71 11 80
Fax number : +33 2 43 71 16 51
www.alroc.fr

Pliers for MV cable outer sheath

TO DO WHAT

The PG3HTA/2530 enables the user to make a circular and longitudinal cut in order to remove cable's outer sheath

All cutting depth ranging from 0,5 mm / 0,019 in to 5 mm / 0,196 in are available on demand

How to built your customized pliers : PG3HTA/yyzz

yy = Circular cutting depth e.g : 25 = 2,5 mm / 0,098 in

zz = Longitudinal cutting depth e.g : 30 = 3,0 mm / 0,118 in

**Options**

SGM - Large size pouch

Spare part

MTC3/25 - Spare blade for circular cutting 2,5 mm / 0,098 in (x4)

MTL3/30 - Spare blade for longitudinal cutting 3,0 mm / 0,118 in

Associated tool

MF1+/25 - Multifunction tool for bonded semiconductor

MF2/40 - Multifonction tool for outer sheath and insulation



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Circular cutting thickness capacity	Longitudinal cutting thickness capacity	Length	Width	Height	
PG2HTA/2828	21 - 35 mm 0,827 - 1,378 in	2,8 mm / 0,110 in	2,8 mm / 0,110 in	240 mm 9,449 in	85 mm 3,346 in	80 mm 3,150 in	box
PG3HTA/2530	26 - 52 mm 1,024 - 2,047 in	2,5 mm / 0,098 in	3,0 mm / 0,118 in	265 mm 10,433 in	95 mm 3,740 in	80 mm 3,150 in	box
PG3HTA/2828	26 - 52 mm 1,024 - 2,047 in	2,8 mm / 0,110 in	2,8 mm / 0,110 in	240 mm 9,449 in	85 mm 3,346 in	80 mm 3,150 in	none
PG3HTA/2833	26 - 52 mm 1,024 - 2,047 in	2,8 mm / 0,110 in	3,3 mm / 0,130 in	265 mm 10,433 in	95 mm 3,740 in	80 mm 3,150 in	none
PG4HTA/3033	47 - 75 mm 1,850 - 2,953 in	3,0 mm / 0,118 in	3,3 mm / 0,130 in	300 mm 11,811 in	110 mm 4,331 in	105 mm 4,134 in	none
PG4HTA/3035	47 - 75 mm 1,850 - 2,953 in	3,0 mm / 0,118 in	3,5 mm / 0,138 in	300 mm 11,811 in	110 mm 4,331 in	105 mm 4,134 in	box
PG5HTB/3535	69 - 95 mm 2,717 - 3,740 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	360 mm 14,173 in	140 mm 5,512 in	160 mm 6,299 in	none
PG6HTB/3535	90 - 125 mm 3,543 - 4,921 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none
PG6HTB/4040	90 - 125 mm 3,543 - 4,921 in	4,0 mm / 0,157 in	4,0 mm / 0,157 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none
PG7HTB/3535	120 - 170 mm 4,724 - 6,693 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none