



Selectively Coated Ball-Lok Ties



Manufactured in the UK from 316 SS, the selectively coated Ball-Lok ties offer the same benefits as the full coated version but is ideal where Nylon 11 coating is required.

- Self locking operation for fast, easy application
- Two widths – 4.6mm & 7.9mm
- 316 Stainless steel with Nylon 11 coating
- Corrosion, UV and weather resistant
- Smooth inside diameter
- Zero halogen, low smoke



K502 / KE922

See pages 26-29 for full details on TOOLS and their specifications.



316 Stainless Steel Selectively Coated Ball-Lok Ties Pack Qty – 100 (bag)

PART NUMBER	MAX. BUNDLE DIAMETER		APPROX LENGTH		APPROX WIDTH		APPROX WEIGHT PER 100		MIN. LOOP TENSILE STRENGTH	
	INCH	MM	INCH	MM	INCH	MM	LBS	KGS	LBS	N
KE0618	1.2	30	5.9	150	0.18	4.6	0.55	0.25	100	445
KE0628	2.0	50	7.9	201			0.62	0.28		
KE0638	2.7	69	10.2	259			0.75	0.34		
KE0648	4.0	102	14.2	360			1.01	0.46		
KE0658	6.0	152	20.4	520			1.41	0.64		
KE0668	8.0	203	26.8	679			1.80	0.82		
KE0678	10.0	254	33.0	838			2.33	1.06		
KE0818	1.2	30	5.9	150	0.31	7.9	1.02	0.46	120	534
KE0828	2.0	50	7.9	201			1.16	0.53		
KE0838	2.7	69	10.2	259			1.50	0.68		
KE0848	4.0	102	14.2	360			1.78	0.81		
KE0858	6.0	152	20.4	520			2.46	1.12		
KE0868	8.0	203	26.8	679			3.17	1.44		
KE0878	10.0	254	33.0	838			3.83	1.74		



Underwriters Laboratories Listing on this product.