



Multi-Lok Ties



A high strength, vibration resistant tie. This product is a perfect choice for harsh duty or marine environments.

- Self-locking ties
- 316 stainless steel
- Uncoated or nylon coated versions available
- Two widths – 7mm and 12mm
- Install by hand or with a variety of tools
- Unique high strength multiple locking system
- Vibration proof



M503 / KE922 / AE200 / AE201

See pages 26-29 for full details on TOOLS and their specifications.



Multi-Lok Ties – Coated

PART NUMBER	MATERIAL	WIDTH		LENGTH		PACKAGED WEIGHT		MAX. DIAMETER SINGLE WRAP		MIN. LOOP TENSILE STRENGTH (LBS)	PACKAGE QTY
		IN	MM	IN	MM	LBS	KGS	IN	MM		
AE611	316 SS	0.276	7.0	6.0	150	0.7	0.3	1.3	33	250	100/Bag
AE612	316 SS	0.276	7.0	9.0	225	0.9	0.5	2.2	57	250	100/Bag
AE613	316 SS	0.276	7.0	12.0	300	1.3	0.6	3.2	81	250	100/Bag
AE614	316 SS	0.276	7.0	18.0	450	1.8	0.8	5.1	129	250	100/Bag
AE615	316 SS	0.276	7.0	24.0	610	2.6	1.2	7.1	180	250	100/Bag
AE711	316 SS	0.472	12.0	6.0	150	1.1	0.5	1.3	33	415	100/Bag
AE712	316 SS	0.472	12.0	9.0	225	1.7	0.8	2.2	57	415	100/Bag
AE713	316 SS	0.472	12.0	12.0	300	2.2	1.0	3.2	81	415	100/Bag
AE714	316 SS	0.472	12.0	18.0	450	3.0	1.4	5.1	129	415	100/Bag
AE715	316 SS	0.472	12.0	24.0	610	4.3	2.0	7.1	180	415	100/Bag



Multi-Lok Ties – Uncoated

PART NUMBER	MATERIAL	WIDTH		LENGTH		PACKAGED WEIGHT		MAX. DIAMETER SINGLE WRAP		MIN. LOOP TENSILE STRENGTH (LBS)	PACKAGE QTY
		IN	MM	IN	MM	LBS	KGS	IN	MM		
AE601	316 SS	0.276	7.0	6.0	150	0.7	0.3	1.3	33	250	100/Bag
AE602	316 SS	0.276	7.0	9.0	225	0.9	0.5	2.2	57	250	100/Bag
AE603	316 SS	0.276	7.0	12.0	300	1.3	0.6	3.2	81	250	100/Bag
AE604	316 SS	0.276	7.0	18.0	450	1.8	0.8	5.1	129	250	100/Bag
AE605	316 SS	0.276	7.0	24.0	610	2.6	1.2	7.1	180	250	100/Bag
AE701	316 SS	0.472	12.0	6.0	150	1.1	0.5	1.3	33	415	100/Bag
AE702	316 SS	0.472	12.0	9.0	225	1.7	0.8	2.2	57	415	100/Bag
AE703	316 SS	0.472	12.0	12.0	300	2.2	1.0	3.2	81	415	100/Bag
AE704	316 SS	0.472	12.0	18.0	450	3.0	1.4	5.1	129	415	100/Bag
AE705	316 SS	0.472	12.0	24.0	610	4.3	2.0	7.1	180	415	100/Bag

