




Pan-Ty® Cable Ties – Nylon 6.6

- For indoor use
- Versatile cable ties can be used in countless applications
- One-piece construction for consistent performance and reliability
- Among the lowest threading force of any one-piece cable tie in the industry
- Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speed installation
- A variety of materials and colors available for specific applications
- UL Listed for use in plenum or air handling spaces per NEC except PLT.6SM and PLT5H/6H/8H/13H



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N			

Subminiature Cross Section

PLT.6SM-C	2.8	71	0.070	1.8	0.030	0.8	0.60	15	8	36	GTS-E, PTS	100	1000
-----------	-----	----	-------	-----	-------	-----	------	----	---	----	------------	-----	------

Miniature Cross Section – Plenum-Rated

PLT.7M-C	3.1	79	0.090	2.3	0.032	0.8	0.68	17	18	80	GTS-E, GS2B, PTS, PPTS, STS2	100	1000
PLT1M-C	3.9	99	0.098	2.5	0.043	1.1	0.87	22	18	80		100	1000
PLT1.5M-C	5.6	142	0.098	2.5	0.043	1.1	1.25	32	18	80		100	1000
PLT2M-C	8.0	203	0.098	2.5	0.043	1.1	2.00	51	18	80		100	1000

Intermediate Cross Section – Plenum-Rated

PLT1.5I-C	5.6	142	0.142	3.6	0.045	1.1	1.38	35	40	178	GTS-E, GS2B, PTS, PPTS, STS2	100	1000
PLT2I-C	8.0	203	0.142	3.6	0.045	1.1	2.00	51	40	178		100	1000
PLT2.5I-C	9.7	246	0.145	3.7	0.052	1.3	2.50	64	40	178		100	1000
PLT3I-C	11.4	290	0.145	3.7	0.052	1.3	3.00	76	40	178		100	1000
PLT4I-C	14.5	368	0.145	3.7	0.052	1.3	4.00	102	40	178		100	1000

Standard Cross Section – Plenum-Rated NEW! UL TYPE 2S Rated

PLT1S-C	4.8	122	0.190	4.8	0.052	1.3	1.00	25	50	222	GTS-E, GS2B, GTH-E, GS4H, PTS, PPTS, PTH, STS2, STH2	100	1000
PLT1.5S-C	6.2	157	0.190	4.8	0.052	1.3	1.50	38	50	222		100	1000
PLT2S-C	7.4	188	0.190	4.8	0.052	1.3	1.88	48	50	222		100	1000
PLT2.5S-C	9.8	249	0.190	4.8	0.052	1.3	2.50	64	50	222		100	1000
PLT3S-C	11.5	292	0.190	4.8	0.052	1.3	3.00	76	50	222		100	1000
PLT4S-C	14.5	368	0.190	4.8	0.052	1.3	4.00	102	50	222		100	1000
PLT4.5S-C	15.5	394	0.190	4.8	0.052	1.3	4.50	114	50	222		100	1000
PLT5S-C	17.5	445	0.190	4.8	0.052	1.3	5.00	127	50	222		100	500

Light-Heavy Cross Section (Straight Tip) – Plenum-Rated

PLT2H-L	8.1	206	0.300	7.6	0.075	1.9	2.00	51	120	534	GTH-E, GS4H, GS4EH, PTH, STH2, ST3EH	50	500
PLT2.5H-L	9.8	251	0.300	7.6	0.075	1.9	2.50	64	120	534		50	500
PLT3H-L	11.4	290	0.300	7.6	0.075	1.9	3.00	76	120	534		50	500
PLT4H-L	14.5	368	0.300	7.6	0.075	1.9	4.00	102	120	534		50	500
PLT6LH-L	21.9	556	0.300	7.6	0.075	1.9	6.00	152	120	534		50	500
PLT7LH-L	24.7	627	0.300	7.6	0.075	1.9	7.00	178	120	534		50	500
PLT8LH-L	27.6	701	0.300	7.6	0.075	1.9	8.00	203	120	534		50	500
PLT9LH-L*	30.5	775	0.300	7.6	0.075	1.9	9.00	229	120	534		50	500
PLT10LH-L*	34.3	871	0.300	7.6	0.075	1.9	10.31	262	120	534		50	1000


Heavy Cross Section (Straight Tip)

PLT5H-L*	17.7	450	0.350	8.9	0.078	2.0	5.00	127	175	778	GTH-E, GS4H, GS4EH, PTH, STH2, ST3EH	50	500
PLT6H-L*	20.9	530	0.350	8.9	0.078	2.0	6.00	152	175	778		50	500
PLT8H-L*	30.6	779	0.350	8.9	0.078	2.0	9.00	229	175	778		50	500
PLT13H-Q*	43.3	1100	0.350	8.9	0.078	2.0	13.00	330	175	778		25	500

*UL Listed – meets the requirements of UL 181B-C, for securing UL Listed non-metallic air ducts and air connectors.

UL LISTED Pan-Ty® Lashing Ties – Nylon 6.6

- For indoor use
- Typically used for heavy duty applications
- Among the strongest Pan-Ty® Cable Tie available
- Can be used with MCEH mounting clip, see page B1.22
- UL Listed for use in plenum or air handling spaces per NEC



Part Number	Length		Width		Thickness		Max. Bundle Dia.		Min. Loop Tensile Str.		Recommended Installation Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	In.	mm	In.	mm	In.	mm	In.	mm	Lbs.	N			
Extra-Heavy Cross Section													
PLT2EH-C	9.0	229	0.500	12.7	0.075	1.9	2.00	51	250	1112	GS4EH, ST3EH	100	1000
PLT5EH-Q	20.1	511	0.500	12.7	0.075	1.9	5.00	127	250	1112		25	250
PLT6EH-Q	22.2	564	0.500	12.7	0.075	1.9	6.00	152	250	1112		25	250
PLT8EH-C	28.3	719	0.500	12.7	0.085	2.2	8.00	203	250	1112		100	1000
PLT10EH-C	34.2	869	0.500	12.7	0.085	2.2	10.00	254	250	1112		100	500
PLT12EH-C	40.1	1019	0.500	12.7	0.085	2.2	12.00	305	250	1112		100	500