


MONI-PT100-EXE-SENSOR

nVent

RAYCHEM

TEMPERATURE SENSOR FOR HAZARDOUS AREA (WITHOUT JUNCTION BOX)




Certified EEx e II cable gland preinstalled on the sensor lead (M16, Brass, inclusive sealing washer, locknut and earth tag)

AREA OF USE

Hazardous environment Zone I

APPROVALS

Baseefa11ATEX0070X

 II 2 GD

Ex e IIC T6 Ta -50°C to +60°C Gb

Ex tb IIIC T85°C Ta -50°C to +60°C Db IP66

IECEX BAS 11.0035X

Ex e IIC T6 Ta -50°C to +60°C Gb

Ex tb IIIC T85°C Ta -50°C to + 60°C Db IP66

EAC 

TC RU C-BE.IM43.B.01764

000 "TexИмпорт"

1Ex e IIC T6 Gb X

Ex tb IIIC T85°C Db X

IP66 Ta -60°C...+60°C

Made in GB

SENSOR

Type	Pt 100 (3 wire) DIN IEC 751, Class B.
Material	Stainless steel (MI).
Temperature measuring range	-100°C to +500°C
Maximum exposure temperature	+585°C
Length	2 m
Diameter	ca 3 mm
Minimum bending radius	extension cable: 20 mm, the measuring tip should not be bent

INSTALLATION AND CONNECTION

M16 (Brass) compression gland pre-installed on the sensor.

Sealing washer, earth tag and locknut included.

Maximum operating temperature (for the gland) -50°C to +60°C

ORDERING DETAILS

Part Description	nVent RAYCHEM MONI-PT100-EXE-SENSOR
PN (Weight)	529022-000 (0.11 kg)

North America

Tel +1.800.545.6258
Fax +1.800.527.5703
thermal.info@nVent.com

Europe, Middle East, Africa

Tel +32.16.213.502
Fax +32.16.213.604
thermal.info@nVent.com

Asia Pacific

Tel +86.21.2412.1688
Fax +86.21.5426.3167
cn.thermal.info@nVent.com

Latin America

Tel +1.713.868.4800
Fax +1.713.868.2333
thermal.info@nVent.com



nVent.com

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER