



**PCB Accessories Industrial Power Relays RZ, RT, RP and SR2M**

**Sockets for PCB mount**

**RT78601**, Socket with PCB terminals, pinning 3.5 mm




**RT78602**, Socket with PCB terminals, pinning 5 mm



**PCB layout**

Bottom view on solder pins



**Approvals**


cULus E135149, VDE: 40007571 (in combination with RT), 40023970 (in combination with RZ), 40025448 (in combination with RP), 116064 (in combination with SR2M)

**Technical data**


**RT78601/RT78602**

|                             |                            |
|-----------------------------|----------------------------|
| Rated voltage               | 250VAC                     |
| Rated current               | see following table        |
| Limiting continuous current | see derating curves beside |


**Derating curve RT78601**



**Derating curve RT78602**



**Derating curve RT78602**



| RATED CURRENT | 1860990-1 / RT78601<br>Single Pinning<br>(bottom view on solder pins)  | 1860991-1 / RT78602<br>Double Pinning<br>(bottom view on solder pins)  |
|---------------|--|--|
|               | 16A  |  |
| 10A           |  | <ul style="list-style-type: none"> <li>RP 1pole version (RP3)</li> </ul>   |
| 8A            | <ul style="list-style-type: none"> <li>RZ01-...-R (reinforced flux proof version)</li> <li>RT 1pole version (RT1)</li> </ul> | <ul style="list-style-type: none"> <li>RZ02-...-R (reinforced flux proof version)</li> <li>RT 1pole version (RT2)</li> </ul> |
| 2 x 8A        |  | <ul style="list-style-type: none"> <li>RT 2pole version (RT4)</li> </ul>   |
| 2 x 6A        |  | <ul style="list-style-type: none"> <li>SR2M Plug-In (P1 version)</li> </ul>  |
| 5A            | <ul style="list-style-type: none"> <li>RP 1pole version (RP4)</li> </ul>   | <ul style="list-style-type: none"> <li>RP 1pole version (RP4)</li> </ul>   |
| 2 x 5A        |  | <ul style="list-style-type: none"> <li>RP 2pole version (RP4)</li> </ul>   |

**PCB Accessories Industrial Power Relays RZ, RT, RP and SR2M (continued)**

| Technical data (continued)  |  | RT78601/RT78602               |
|---|--|-------------------------------|
| Initial dielectric strength   |  |                               |
| coil-contact circuit  |  | 4000 V <sub>ms</sub>          |
| open contact circuit  |  | 1000 V <sub>ms</sub>          |
| adjacent contact circuits   |  | 2500 V <sub>ms</sub>          |
| Clearance / creepage  |  |                               |
| coil-contact circuit  |  | ≥ 8/8mm                       |
| coil-contact circuit without mounting screw   |  | ≥ 10/10mm                     |
| Material group of insulation parts  |  |                               |
|   |  | IIIa                          |
| Insulation to IEC 60664-1   |  |                               |
| Type of insulation  |  |                               |
| coil-contact circuit  |  | reinforced                    |
| open contact circuit  |  | functional                    |
| adjacent contact circuits   |  | functional                    |
| Rated Insulation voltage  |  | 250 V                         |
| Pollution degree  |  | 2                             |
| Overvoltage category  |  | III                           |
| Material compliance: EU RoHS/ELV, China RoHS, REACH, Halogen content refer to the Product Compliance Support Center at <a href="http://www.te.com/customersupport/rohssupportcenter">www.te.com/customersupport/rohssupportcenter</a> |  |                               |
| Ambient temperature range   |  | -40...+85°C (relay dependent) |
| Terminals   |  | PCB                           |
| Insertion cycles  |  | A (10)                        |
| Max. Insertion Force total  |  | 100 N                         |
| Mounting distance   |  | ≥ 0, dense packing            |
| Resistance to soldering heat  |  | 270°C / 10 s                  |
| Weight  |  | 3 g                           |
| Packaging unit  |  | 100 pcs                       |

1) for 1 pole relays with load current greater than 8A the relay terminals 11-21, 12-22 and 14-24 have to be bridged on the PCB

**Combination of relay and socket, insulation requirements and thermal characteristics**

The relay standard IEC 61810-1 has an important impact on the combination of a relay and the respective socket. The relay sockets have to comply with the requirements of IEC 61984 and the insulation requirements of the IEC 61810-1. Even if the socket alone fulfills or exceeds the insulation requirements as clearance/creepage for the relay, the combination of a relay with a socket may reduce the creepage and lead to a lower rated insulation voltage. Hence restrictions for the combination relay-socket may be the consequence, e.g. a reduction of the voltage range or of the pollution degree. Especially for miniature multi-pole relay and respective sockets with small distance between the contact circuits, these restrictions have a big impact.

Apart from the insulation properties, the thermal characteristics of the combination relay and socket are of utmost importance (see > 'Derating curves'). Especially the operations conditions like multiple heat up and cool down cycles could have significant impact on the long-term stability of the contact resistance of the combination contact tulip and terminal, and may thereby cause risk of overheating and fire hazard. It is strongly recommended that such conditions are considered in the design and usage of the device and that the devices are thoroughly tested under real conditions.

As sockets from different sources are not directly comparable, the compliance with the technical specification can only be informed for an approved combination relay-socket. As design details and characteristics for non TE products are beyond our control, confirmations for technical parameters and characteristics regarding such combinations is not possible. Risks as reduced dielectric strength, fire hazard, etc. due to use based on unclear or omitted data, limitations or restrictions must not be underestimated.

NOTE: We only confirm the characteristics and parameters for the approved combinations of relays and sockets as indicated in the catalog and datasheets.

| Sockets with PCB terminals |   |             |
|----------------------------|---|-------------|
| Type                       |   | Part Number |
| <b>RT78601</b>             | Socket with PCB terminals, pinning 3.5 mm | 1860990-1   |
| <b>RT78602</b>             | Socket with PCB terminals, pinning 5 mm   | 1860991-1   |

| Accessories for RT78601, RT78602 |   |             |
|----------------------------------|---|-------------|
| Type                             |   | Part Number |
| <b>RT16C01</b>                   | Plastic retaining clip, relay height 15.7 mm  | 1860995-1   |
| <b>RT28516</b>                   | Metal retaining clip RT, relay height 15.7 mm | 1419108-7   |
| <b>RP16C01</b>                   | Plastic retaining clip, relay height 25.5 mm  | 1860996-1   |
| <b>RP28500</b>                   | Metal retaining clip, relay height 25.5 mm    | 1-1393161-9 |

Recommended mounting screw: M3 cylinder-head screw with internal hexagon according DIN 912